

- Built-in fire protection system.
- Scalable expansion up to 15 pcs in parallel.
- Built-in WiFi for remote monitor the battery pack data.
- LiFePO4: Higher safe performance and longer cycle life.
- Multiple Protection with built-in smart BMS, breaker and fuse.
- Compatible with leading inverter brands.
- Up to 7-year long warranty.




FLA48100



FLA48200













Model	FLA48100	FLA48200
Battery Type	LiFePO4	
Nominal Energy	5.12kWh	10kWh
Nominal Voltage	51.2V	51.2V
Operating Voltage	44.8-57.6V	44.8-57.6V
Recommend Charge/Discharge Current[1]	≤100A	≤120A
Recommend Charge/Discharge Power[1]	≤5,000W	≤6,000W
Maximum Charge/Discharge Current(15s)	150A	150A
Maximum Charge/Discharge Power(15s)	7,500W	7,500W
Scalability	Max. 15 pcs in Parallel(76.8kWh)	Max. 15 pcs in Parallel(150kWh)
Depth of Discharge(DOD)	≥95%	
Communication	RS485/CAN	
Protection Degree	IP21	
Cycle Life	≥ 6000 Cycles (25°C±2°C,0.5C/0.5C,90%DOD,70%EOL)	
Charging Temperature Range	0°C~+55 °C	
Discharging Temperature Range	-20°C~+55°C	
Display Type	LCD+LED	
Installation	Wall-Mounted / Floor-Mounted	
Protection	Built-in smart BMS, Breaker, Fuse	
Warranty Period	7 Years	
Certification	UN38.3、CE-EMC、 IEC 62619	UN38.3、CE-EMC、 IEC 62619、CB
Product Weight	48KG	68KG
Package Weight	55KG	88KG
Product Dimension	663X400X178MM	735X433X188MM
Package Dimension	782X522X262MM	849X550X362MM

 $^{{}^*}Product \, specifications \, may \, vary \, during \, continuous \, improvements. \, Please \, contact \, us \, for \, latest \, details.$

Product Display



Built-in WiFi / Bluetooth for Remote Monitoring



Aerosol Fire Extinguishing System



Support Wall Mounted Installation



Wide Inverter Compatibility











^{*}Refer to Felicitysolar's Warranty Policy for applicable conditions.